

## RISER TUBES

### COPPER – FAUCET & TOILET ("A", "DL", "DE" & "3DL" Style)

<b>Use:</b>	Supply riser tube for potable water distribution systems.
<b>Sizes:</b>	3/8", 7/16" and 1/2" O.D.
<b>Lengths:</b>	For 12", 15", 20", 30" and 36" connectors. See catalog for specific lengths.
<b>Operating Pressure:</b>	125 psi maximum
<b>Operating Temperature:</b>	40 to 180°F
<b>Material Specifications:</b>	Tube – C12200 copper tubing as per ASTM B-68.  Seal washers (DL risers) – Santoprene™.  Plastic support in lavatory types - POM.  Other nosepiece types – Nitrile rubber.
<b>Designed and Manufactured in Accordance With:</b>	ASME A112.18.1 ANSI/NSF 61
<b>Approvals/Listings:</b>	IAPMO File #0645 UL Approved to NSF 61 - File #MH25826 State of Massachusetts

*This technical product data sheet and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This technical product data sheet must be returned to BrassCraft if requested.*

Tech. Product Data Sheet Number	© 2006 BrassCraft Mfg.	Revision Level
800.21	Page 1 of 1	(B)