

WATER CONNECTORS

SPEEDI ONE PLUS™

Use:	For use with potable hot & cold water. Sink riser, water closet and dishwasher installations. Supply stop for potable water distribution systems.
Sizes:	A variety of end fittings with lengths from 9 to 72 inches. See catalog for specific combinations. Standard connector: I.D. 0.300", O.D. 0.517"
Operating Pressure:	125 psi maximum
Operating Temperature:	40 – 140°F, 180°F Intermittent.
Material Specifications:	Nuts: C36000 brass, POM. End Fittings: C36000 brass. Braiding: Polyvinyl Chloride Coated Polyester Yarns. Tubing: Reinforced PVC Washers: Nitrile Rubber. Body and other brass components: C36000 brass. Stem: POM. Washers: Bib and packing washers, Nitrile or EPDM rubber. Handle: Lexan®
Flexible Connector Designed and Manufactured in Accordance With:	ASME A112.18.6 ANSI/NSF 61 CSA-B125
Approvals/Listings:	IAPMO File #0452 State of Michigan File 1417-PA Listed by UL as complying with ANSI/NSF 61 - File #MH25826 City of New York, Dept. of Buildings, MEA 209-97-E CSA Approved File #150436

This technical product data sheet and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This technical product data sheet must be returned to BrassCraft if requested.

Tech. Product Data Sheet Number	© 2006 BrassCraft Mfg.	Revision Level
800.31	Page 1 of 1	(B)