



CSSC Type of Connector

CSSB	Coated Stainless Steel - 3/4" I.D. (7/8" O.D.) Tube
CSSC	Coated Stainless Steel - 1/2" I.D. (5/8" O.D.) Tube
CSSD	Coated Stainless Steel - 3/8" I.D. (1/2" O.D.) Tube
CSSL	Coated Stainless Steel - 1/4" I.D. (3/8" O.D.) Tube
CSST	Coated Stainless Steel - 1/4" I.D. (3/8" O.D.) Tube, Fine Thread Nuts

54E- End Fitting/Valve Style and Size

Fittings:

- 3/4" M.I.P. Straight (tapped 1/2" F.I.P.)
- 3/4" F.I.P. Straight
- 3/4" F.I.P. Elbow
- 1/2" M.I.P. Straight (tapped 3/8" F.I.P.)
- 1/2" F.I.P. Straight
- 1/2" F.I.P. Elbow (for CSSL)
- 3/8" M.I.P. (tapped 1/8" F.I.P.) for CSSD / SSD and CSSL / SSL connectors only.
- 3/8" F.I.P. Straight
- 5/8" Female Flare Straight*
- 3/4" M.I.P. Straight (tapped 1/2" Female Flare)*
- 1/2" M.I.P. Straight (tapped 3/8" Female Flare)*
- 1" M.I.P. Straight (tapped 3/4" F.I.P.)
- 1" F.I.P. Straight
- Nut x Nut (connector sold less fittings)**

Ball Valves:

- | | |
|---|--|
| J | 3/4" F.I.P. Straight |
| K | 1/2" F.I.P. Straight |
| M | 1/2" F.I.P. Straight
(for CSSL connectors only) |
| P | 3/4" F.I.P. Angle |
| R | 1/2" F.I.P. Angle |

NOTE: "E" suffix denotes Safety+PLUS valve

- * Available in Safety+PLUS only
- ** NON-Certified Gas Connector

48 Nominal Connector Length in Inches

Standard Lengths: 12", 18", 24", 30", 36", 48", 60", and 72"

Nominal length includes adaptors. Connectors with valves are approximately 1" longer.



EXAMPLE: CSSC54E-48

CSSC - Coated Stainless Steel - 1/2" I.D. (5/8" O.D.) Tube

54E - 1/2" F.I.P. (3/4" M.I.P.) Safety+PLUS Inlet x
1/2" M.I.P. Outlet

48 - 48" Length