

## WATER SUPPLY STOPS

### 1/4 TURN G2 SureConnect™ STOP

<b>Use:</b>	¼-turn supply stop for potable water distribution systems.
<b>Sizes:</b>	See catalog for specific configurations.
<b>Operating Pressure:</b>	125 psi maximum
<b>Operating Temperature:</b>	40 - 150°F Maximum continuous use temperature: 115°F
<i>Note: Not intended for recirculating water systems that produce continuous use temperatures above 115°F. For those applications, use BrassCraft KT series ball stops.</i>	
<b>Material Specifications:</b>	<p>Body and brass components – Chrome Plated C36000 Brass</p> <p>Stem – Barrel - Santoprene</p> <p style="padding-left: 40px;">Shaft - Glass Filled Polypropylene</p> <p>Stem O-Ring - EPDM</p> <p>Retainer O-Ring – EPDM (straight valves)</p> <p>Retainer – Glass Filled Polyphthalamide (straight valves)</p> <p>Handle - Zinc Die Cast</p> <p>Handle Screw - Zinc Plated Steel</p> <p>Compression Sleeve – C36000 Brass</p> <p>SureConnect™ O-Ring – Viton</p> <p>SureConnect™ O-Ring – Nitrile</p> <p>SureConnect™ O-Ring Spacer – Nylon</p> <p>Housing – Glass Filled Nylon</p> <p>Housing Retainer – Glass Filled Nylon</p> <p>Anti-Rotation Disk – C36000 Brass</p> <p>Inner Spacer – C36000 Brass</p>
<b>Designed and Manufactured In Accordance With:</b>	<p>By IAPMO to ASME A112.18.1-2005</p> <p>By CSA to CSA-B125-05</p> <p>By CSA to NSF 61 Section 9</p>
<b>Approvals/Listings:</b>	<p>IAPMO File #0645</p> <p>CSA Approved – File #0204593</p>

*This technical product data sheet and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This technical product data sheet must be returned to BrassCraft if requested.*

Tech. Product Data Sheet Number	© BrassCraft Mfg.	Revision Level
800.47	Page 1 of 1	(A)