

TOILET REPAIR

HORNET FLAPPERS I, V, X

Use:	Flapper which seals water closet, toilet tank from bottom toilet bowl.
Installation:	Universal Fit - Hornet I - For use with standard and non-standard flush valves. - Hornet V - For use with standard and non-standard flush valves, including Crane flush valves. - Hornet X - For use with standard and non-standard flush valves, including Crane flush valves.
Operating Pressure:	0-24" W.C.
Operating Temperature:	40-80°F (room temperature)
Material Specifications:	Hornet I - Nitril rubber + Styrene Butadiene Hornet V - Polyvinyl Chloride (Flexible PVC) Hornet X - Ethylene Propylene Diene Methylene (EPDM) Clear Sleeve - Polyvinyl Chloride material (PVC) Chain - Polypropylene+40% glass fiber Hook - Polypropylene+40% glass fiber
Designed and Manufactured In Accordance With:	ANSI/ASME A112.19.5
Approvals/Listings:	N/A

This technical product data sheet and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This technical product data sheet must be returned to BrassCraft if requested.

Tech. Product Data Sheet Number	© 2006 BrassCraft Mfg.	Revision Level
800.39	Page 1 of 1	(B)