



ITEM I.D.	INLET	DIM 'A'	DIM 'B'
8500	COPPER SWEAT	4.56/4.50	.625 ϕ
8503	3/8 PEX	2.41/2.35	.500 ϕ
8504	1/2 PEX	2.41/2.35	.500 ϕ
8514	1/2 PEX FOR COLD EXPANSION	2.85/2.79	.625 ϕ
8515	COPPER SWEAT	6.56/6.50	.625 ϕ
8519	COPPER SWEAT	21.06/21.00	.625 ϕ
8520	1/2 PEX	9.06/9.00	.625 ϕ
8521	1/2 PEX FOR COLD EXPANSION	9.06/9.00	.625 ϕ

This drawing and all data contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This drawing must be returned to BrassCraft if requested.

BrassCraft
A Masco Company
NOVI, MICHIGAN

ALL GOVT PER ANSI STD Y14.5M
CLASSIFICATION OF QUALITY LEVELS

KPC (KEY PRODUCT CHARACTERISTICS) \diamond
STPC (STANDARD PRODUCT CHARACTERISTICS) \triangle
PRODUCT MARKINGS \square

DESCRIPTION SURECONNECT STRAIGHT STUB-OUTS (SUBMITTAL)		DRAWING NO. VPG0781C	
DRAWN KLIMKIE	DATE 4/6/2006	MATERIAL	ITEM DESCRIPTION 8500
CHK'D. Schutte	DATE 09/20/2006	VOLUME	ITEM ID 8500
APP'D.	DATE:		SEE CHART
NOTE: UNLESS OTHERWISE SPECIFIED TWO PLACE DECIMALS THREE PLACE DECIMALS ANGULARITY		UNITS INCH	SCALE: (UNLESS NOTED) 2:1
SIZE		REV. C	