


## WATER CONNECTORS

### SPEEDI-PLUMB® - VINYL

<b>Use:</b>	For use with potable hot & cold water. Sink riser, water toilet installations.
<b>Sizes:</b>	A variety of end fittings with lengths from 9 to 72 inches. See catalog for specific combinations.  I.D. .300", O.D. .500"
<b>Operating Pressure:</b>	125 psi maximum
<b>Operating Temperature:</b>	40 – 140°F intermittent to 180°F
<b>Material Specifications:</b>	Tubing – Polyvinyl Chloride with Polyester yard braid reinforcement.  Nuts: C36000 brass or Polypropylene  End Fittings – C36000 brass  Ferrule: Zinc plated 1008 steel  Washers – Nitrile.
 <b>Compliant Product Material</b> <b>Verified for Low Lead and Plumbing Products</b> <b>Covers California and Vermont requirements</b>	End Fittings – C37000 brass
<b>Designed and Manufactured In Accordance With:</b>	ASME A112.18.6 ANSI/NSF 61 CSA B125
<b>Approvals/Listings:</b>	IAPMO File #0452 State of Michigan File 1417-PA Listed by UL as complying with ANSI/NSF 61 - File #MH25826 City of New York, Dept. of Bldg., MEA 209-97-E CSA Approved File # 204593 CSA Approved to AB1953 – Project #2174785

*This technical product data sheet and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This technical product data sheet must be returned to BrassCraft if requested.*

Tech. Product Data Sheet Number	© 2006 BrassCraft Mfg.	Revision Level
800.33	Page 1 of 1	(C)