

WATER SUPPLY STOPS

1/4 TURN G2 STOP - BRASS

Use:	Supply stop for potable water distribution systems.
Sizes:	See catalog for specific configurations.
Operating Pressure:	125 psi maximum
Operating Temperature:	40 - 140°F Maximum continuous use temperature: 115°F
<i>Note: Not intended for recirculating water systems that produce continuous use temperatures above 115°F. For those applications, use BrassCraft KT series ball stops.</i>	
Material Specifications:	Body and brass components – C36000 brass Stem – Barrel - Santoprene Shaft - Glass Filled Polypropylene Stem O-Ring - EPDM Retainer O-Ring - EPDM (straight valves) Retainer - Glass Filled Polypropylene (straight valves) Handle - Zinc Die Cast Handle Screw - Zinc Plated Steel
Compliant Product Material Verified for Low Lead and Plumbing Products Covers California and Vermont requirements	Body - C69300 brass
Designed and Manufactured In Accordance With:	By IAPMO to ASME A112.18.1 By CSA to CSA-B125 By UL to NSF 61 Section 9
Approvals/Listings:	IAPMO File #0645 CSA Approved – File #0204593 CSA Approved to AB1953 – Project #2174785 UL Approved to NSF61- File #MH25826

This technical product data sheet and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This technical product data sheet must be returned to BrassCraft if requested.

Tech. Product Data Sheet Number	© 2006 BrassCraft Mfg.	Revision Level
800.43	Page 1 of 1	(C)