

WATER CONNECTORS

SureConnect™ DISHWASHER

Use:	For potable water dishwasher installations.
Sizes:	48", 60", and 72" lengths, Standard Connector: ID 0.300", OD 0.550"
Operating Pressure:	125 psi maximum
Operating Temperature:	40 - 140°F intermittent to 180°F
Material Specifications:	Nut: C36000 brass Barb: C36000 brass Ferrule: Zinc Plated Stainless Steel Braiding: Polyvinyl Chloride Coated Polyester Yarns Tubing: Reinforced PVC Flat Washer: Nitrile Rubber SureConnect™ O-Ring – Viton SureConnect™ O-Ring – Nitrile SureConnect™ O-Ring Spacer – Nylon Housing – Glass Filled Nylon Housing Retainer – Glass Filled Nylon Barb Elbow: C36000 Brass
Designed and Manufactured In Accordance With:	ASME A112.18.6 ANSI/NSF 61 CSA B125
Approvals/Listings:	IAPMO File #0645 & #0452 Listed by UL as complying with ANSI/NSF 61 – File #MH25826 CSA Approved – File #0204593

This technical product data sheet and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This technical product data sheet must be returned to BrassCraft if requested.

Tech. Product Data Sheet Number	© BrassCraft Mfg.	Revision Level
800.55	Page 1 of 1	(A)