

GAS APPLIANCE CONNECTORS

ProCoat[®] COATED STAINLESS STEEL GAS APPLIANCE CONNECTORS

Use:	Flexible appliance connector for indoor and outdoor connection of gas appliances to gas piping system. May be used with natural, manufactured, mixed and liquified petroleum (LP or propane) gases and LP gas-air mixtures.
Size:	1 foot to 6 feet -See Catalog
Operating Pressure:	1/2 psi maximum
Operating Temperature:	-40°F to 150°F
Flow Capacity:	Size Dependent -See Capacity Tables
Material Specifications:	<p>Tubing – Type 304 Stainless Steel; austenitic with high chromium content</p> <p>Nuts and End Fittings - Blue zinc-plated 12L14 or 10L10 steel</p> <p>Coating - Polymer-based powder coat</p>
Designed and Manufactured In Accordance With:	<p>(CSSL, CSSD, CSSC, CSSB w/fittings only)</p> <p>ANSI Z21.24 • CSA 6.10 “Connectors for Gas Appliances”*</p> <p>ANSI Z21.75 • CSA 6.27 "Connectors for Outdoor Appliances and Manufactured Housing" (Formerly CSA 3-87)*</p> <p>IAPMO TSC 9-92 (CSSC with capacity in excess of 100,000 BTU/Hour only, CSSB)*</p>
Approvals/Listings:	<p>(CSSL, CSSD, CSSC, CSSB w/fittings only)*</p> <p>CSA Certificate 204593-1139079</p> <p>City of New York MEA 387-90-M</p> <p>AGAL Contract #8204 (Vibration) (SSC Only)</p>
FAQ (Answers to Frequently Asked Questions):	<ul style="list-style-type: none"> Appliance Connectors are for residential and commercial applications, code does not distinguish between them. Gas logs are classified as “decorative gas appliance” and connectors are acceptable. Rule of thumb: Movable gas appliances are usually equipped with wheels or casters for ease of movement. They require connectors meeting ANSI Z21.69 standard. Non-movable appliances that are on feet or legs or are fixed (or bolted) in place, these connectors (Z21.24) are appropriate. The gas connector / gas hose standards are all specific to 1/2 psi system pressure. There is no standard for higher pressure. Connectors are considered complete assemblies only when fittings are included.

* Standards require the connector to include end fittings. Connectors sold without end fittings do not comply with standards and are not "listed" or "approved". Standards only apply to CSSL, CSSD, CSSC and CSSB series connectors only.

<i>This technical product data sheet and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This technical product data sheet must be returned to BrassCraft if requested.</i>		
Tech. Product Data Sheet Number	© 2006 BrassCraft Mfg.	Revision Level
800.12	Page 1 of 1	(C)