


WATER CONNECTORS

INNOFLEX – Nut x Nut

Use:	For use with potable hot & cold water. Risers for Faucet or Toilet Applications.
Sizes:	A variety of end fittings with lengths from 6 to 36 inches. See catalog for specific combinations. 3/8" O.D.
Operating Pressure:	125 psi maximum
Operating Temperature:	40 - 140°F intermittent to 180°F
Material Specifications:	Tubing: 0.205 ID – Cross-Linked Polyethylene (PEX) Nuts: C36000 brass, or Nylon End Fittings: C36000 brass Washers: Nitrile Rubber
 Compliant Product Material Verified for Low Lead and Plumbing Products Covers California and Vermont requirements	End Fittings – C37000 brass
Designed and Manufactured In Accordance With:	ASME A112.18.6 ANSI/NSF 61/9 CSA B125.3 Uniform Plumbing Code
Approvals/Listings:	NSF File #3A190 for: ANSI/NSF 61/9 ASME A112.18.6 CSA B125.3 Uniform Plumbing Code CSA Approved to AB1953 – Project #2174785

<i>This technical product data sheet and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This technical product data sheet must be returned to BrassCraft if requested.</i>		
Tech. Product Data Sheet Number	© BrassCraft Mfg.	Revision Level
800.45	Page 1 of 1	(B)